PRODUCTION SPECIFICATION SUPER 6 - Roadside



Static Note Refer to panel specific dimensions provided on the Campaign Instruction Specs spreadsheet

Artwork Visual size: refer to Campaign Instructions Specs spreadsheet - 1/10 scaling

plus 12mm bleed all sides (no trims)

Actual Visual & Finished size: refer to Campaign Instructions Specs spreadsheet

Accepted Format High resolution Print Ready PDF files (maximum PDF file size of 500MB)

Preferred option is for layered files to be exported with PDF/X-4 setting

Resolution All high resolution images and files are to be supplied 300dpi at artwork size (CMYK)

Black Specification All blacks to be supplied as CMY = 60% and K = 100% (disable overprint)

Fonts All fonts / text to be converted to outlines

File Transfer Print ready PDF to be supplied via FTP

Supplied files/folders to be labelled with 'Campaign ID DesignName'

FTP www.wetransfer.com file sending program approved by Billboards New Zealand for sending artwork

too big to be emailed.

Substrate 450 - 550gsm PVC coated polyester exterior grade Frontlit or Backlit Vinyl (refer to media booking)

Finishing Specific Finishing as per Campaign Instruction Specs spreadsheet

Labelling All material delivered to BBNZ installers MUST be labelled clearly and contain the following:

1. Campaign Name, 2. Panel size & Static Panel number, 3. Qty, 4. Barcode image & number

Deadlines Finished Artwork is required 10 days prior to the campaign start date

Finished Material is required 7 days prior to the campaign start date

